



PRODUCT NAME

# EGR 140 GEAR OIL

PRODUCT CODE

VTP-7002

PRODUCT CATEGORY

AUTOMOTIVE ADDITIVES & LUBRICANTS

Valor's EGR 140, SAE 75W-140 #0428 is a multigrade synthetic (polyalphaolefin), A.P.I. GL-5 rated gear oil formulated to SAE 75W-140 viscosity. It is a premium extreme-pressure lubricant designed for use in axle applications requiring limited-slip performance but can also be used in conventional differentials. Valor EGR 140, SAE 75W-140 is a versatile product that can be used in place of 85w-140, SAE 140 oils and eliminates the need for supplemental friction modifiers such as Ford M2C118-A, Chrysler MS-5630, or GM 1052358. It is designed to provide excellent extreme pressure protection, load carrying capacity, anti-foam performance, corrosion protection, and thermal stability protection.

## APPLICATION

Follow vehicle manufacturer's recommendations for use of product. EGR 140 is designed to be used in conjunction with Valor Differential/ Driveline service equipment and tools.

## FEATURES

Superior lubrication and protection for bearings and gears. Helps prevent wear, pitting, gear noise and corrosion under high-load conditions.

Excellent fluidity and protection in extreme temperatures.

Can be used in conventional differentials in addition to limited slip, avoiding the need for a supplement or application errors.

Contains special additives to reduce chattering in limited-slip differentials.

Meets stringent industry standards, including API GL-5, MT-1 and SAE J2360 specifications.

Recommended for use where Ford M2C-192A, GM 12346140, Chrysler MS-8985, or GL-5 SAE 75W-140 gear oil is specified.



**PACKAGING** FILL: 1 qt. CASE QTY: 12 CASE WT 25.04 lbs.

## SPECIFICATIONS

TEST	ASTM METHOD	TYPICAL RESULTS
Appearance	—	Oil
Color	—	Amber
Odor	—	Petroleum
Specific Gravity @ 68°F	D1298	0.87
Density, US lbs/gal @ 68°F	D1250	7.3
Viscosity, cSt @ 100°C	D445	26
Viscosity Index	D2270	120 (Typical)
Brookfield Viscosity @-40°C, cP	D2983	100,000

